

Pipe Hangers and Supports

Adjustable Swivel Ring Style 702




- VISION style 702 adjustable swivel ring
- meets MSS SP58, SP69 and GB5135.18 requirements.
- Advanced design enhanced strength and minimized deformation under high load.
- Nut with punched head is optional to prevent missing by transportation and installation.
- Hot dip galvanized
- Size: DN15 ~DN200
1/2" ~8"

For complete information please refer to VISION publication 10.01.

Size	Dimensions					Rated Load	Approx. weight
	A	B	C	F	L		
	mm Inches	mm Inches	mm Inches	mm Inches	mm Inches	N Lbf	kg Lbs.
15 1/2	M10 3/8	41 1.61	22 0.87	31 1.22	65 2.56	1335 300	0.04 0.09
20 3/4	M10 3/8	42 1.65	22 0.87	29 1.14	72 2.83	1335 300	0.05 0.11
25 1	M10 3/8	42 1.65	22 0.87	25 0.98	78 3.07	1335 300	0.06 0.13
32 1 1/4	M10 3/8	45 1.77	22 0.87	24 0.94	88 3.46	1335 300	0.06 0.13
40 1 1/2	M10 3/8	49 1.93	22 0.87	25 0.98	95 3.74	1335 300	0.07 0.15
50 2	M10 3/8	63 2.48	22 0.87	33 1.30	105 4.13	1335 300	0.08 0.18
65 2 1/2	M10 3/8	69 2.72	22 0.87	30 1.18	125 4.92	2335 525	0.09 0.20
80 3	M10 3/8	76 2.99	22 0.87	31 1.22	140 5.51	2335 525	0.10 0.22
90 3 1/2	M10 3/8	98 3.86	22 0.87	40 1.57	160 6.30	2335 525	0.11 0.24
100 4	M10 3/8	98 3.86	22 0.87	40 1.57	173 6.81	2893 650	0.17 0.37
125 5	M12 1/2	103 4.06	32 1.26	32 1.26	209 8.23	4450 1000	0.33 0.73
150 6	M12 1/2	137 5.39	32 1.26	53 2.09	249 9.80	4450 1000	0.38 0.84
200 8	M12 1/2	171 6.73	40 1.57	61 2.40	309 12.17	4450 1000	0.57 1.26

- Available with BSPT and NPT thread;
- Style 702R ring with felt is available upon request.



TYPICAL FOR ALL SIZES



Style 702R