

Product Gallery

Material: ASTM A536 GRADE 65-45-12, QT450-10

Threads: ASME b1.20.1, ISO 7-1, GB7306

Size Available: 1" - 12"

Surface Treatment:

P: Painted E: Electroplated S: Epoxy G: Hot-dip Galvanized

Available Color: Red Orange Blue Gray White



XGQT1

Rigid Coupling



XGQT1N

Flexible Coupling



XGQT2

Angle pad Coupling



XGQT1B

Flexible Reducing
Coupling



XGQT08

Grooved Split Flange



XGQT3

Grooved Mechanical Tee



XGQT3S

Threaded Mechanical Tee



XGQT3U

U-bolted Threaded
Mechanical Tee



XGQT01

90° Elbow



XGQT02

45° Elbow



XGQT09

22.5° Elbow



XGQT9

11.25° Elbow



XGQT07

Equal Cross



XGQT7

Grooved Reducing
Cross



XGQT7S

Threaded Reducing
Cross



XGQT06

End Cap



XGQT5

Grooved Concentric
Reducer



XGQT5S

Threaded Concentric
Reducer



XGQT05

Grooved Eccentric
Reducer



XGQT03

Equal Tee



XGQT04

Grooved Reducing Tee



XGQT04S

Threaded Reducing Tee



XGQT8


Adaptor Flange

Product Application

- 1)Automatic sprinkler system for fire protection on commercial ,civil and municipal constructions like water supplying ,gas supplying, heat supplying,etc
- 2)Industrial pipeline system on shipping ,mine, oil field,textile,powder plant,etc.
- 3)Pipeline system on subway station ,railway station ,airport, seaport,bridge,etc




XGQT1 90°Elbow



Nominal Size mm/in	Pipe O.D mm	Working Pressure PSI/Mpa	Dimensions L mm/in	Certificate
25/1	33.7	300/2.07	57/2.24	FM UL
32/1¼	42.4	300/2.07	60/2.36	FM UL
40/1½	48.3	300/2.07	60/2.36	FM UL
50/2	60.3	300/2.07	70/2.75	FM UL
65/2½	73.0	300/2.07	76/3.00	FM UL
65/2½	76.1	300/2.07	76/3.00	FM UL
80/3	88.9	300/2.07	86/3.39	FM UL
100/4	108.0	300/2.07	102/4.02	FM UL
100/4	114.3	300/2.07	102/4.02	FM UL
125/5	133.0	300/2.07	124/4.88	FM UL
125/5	139.7	300/2.07	124/4.88	FM UL
125/5	141.3	300/2.07	124/4.88	—
150/6	159.0	300/2.07	140/5.50	FM UL
150/6	165.1	300/2.07	140/5.50	FM UL
150/6	168.3	300/2.07	140/5.50	FM UL
200/8	219.1	300/2.07	173/6.81	FM UL
250/10	273.0	300/2.07	215/8.46	FM UL
300/12	323.9	300/2.07	245/9.65	FM UL

XGQT02 45°Elbow



Nominal Size mm/in	Pipe O.D mm	Working Pressure PSI/Mpa	Dimensions L mm/in	Certificate
25/1	33.7	300/2.07	44/1.73	FM UL
32/1¼	42.4	300/2.07	44/1.73	FM UL
40/1½	48.3	300/2.07	44/1.73	FM UL
50/2	60.3	300/2.07	51/2.01	FM UL
65/2½	73.0	300/2.07	57/2.24	FM UL
65/2½	76.1	300/2.07	57/2.24	FM UL
80/3	88.9	300/2.07	64/2.52	FM UL
100/4	108.0	300/2.07	76/3.00	FM UL
100/4	114.3	300/2.07	76/3.00	FM UL
125/5	133.0	300/2.07	83/3.27	FM UL
125/5	139.7	300/2.07	83/3.27	FM UL
125/5	141.3	300/2.07	83/3.27	—
150/6	159.0	300/2.07	89/3.50	FM UL
150/6	165.1	300/2.07	89/3.50	FM UL
150/6	168.3	300/2.07	89/3.50	FM UL
200/8	219.1	300/2.07	108/4.25	FM UL
250/10	273.0	300/2.07	121/4.76	—
300/12	323.9	300/2.07	133/5.24	—